

**2000® NM**

Version 1.3      Revision Date: 09/04/2015      SDS Number: 117291-00003      Date of last issue: 08/18/2015  
Date of first issue: 05/18/2015

---

**SECTION 1. IDENTIFICATION**

Product name : 2000® NM

SDS-Identcode : 358G

**Manufacturer or supplier's details**

Company name of supplier : Bestolife Corporation

Address : 2777 N. Stemmons Frwy Ste 1800  
Dallas TX 75207,

Telephone : 855-243-9164/972-865-8961

Telefax : 214-631-3047

Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887  
(24-hours/7 days)

E-mail address : [www.bestolife.com](http://www.bestolife.com)

**Recommended use of the chemical and restrictions on use**

Recommended use : Industrial use  
Thread Compound (Pipe Dope) and Jacking grease for use in  
Offshore industries  
Mining, (without offshore industries)

Restrictions on use : Do not use on oxygen lines or in oxygen enriched  
atmospheres.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Eye irritation : Category 2A

**GHS Label element**

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**  
P264 Wash skin thoroughly after handling.  
P280 Wear eye protection/ face protection.

---

**2000® NM**

Version 1.3      Revision Date: 09/04/2015      SDS Number: 117291-00003      Date of last issue: 08/18/2015  
 Date of first issue: 05/18/2015

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 - < 50
Graphite	7782-42-5	>= 20 - < 30
Talc	14807-96-6	>= 5 - < 10
Calcium oxide	1305-78-8	>= 1 - < 5
12-Hydroxy lithium stearate	7620-77-1	>= 1 - < 5
Quartz	14808-60-7	>= 0.1 - < 1

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
 Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
 Remove contaminated clothing and shoes.  
 Get medical attention.  
 Wash clothing before reuse.  
 Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
 If easy to do, remove contact lens, if worn.  
 Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
 Get medical attention if symptoms occur.  
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Fluorine compounds  
Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding

**2000® NM**

Version 1.3      Revision Date: 09/04/2015      SDS Number: 117291-00003      Date of last issue: 08/18/2015  
 Date of first issue: 05/18/2015

certain local or national requirements.

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
 Do not swallow.  
 Do not get in eyes.  
 Handle in accordance with good industrial hygiene and safety practice.  
 Keep away from water.  
 Protect from moisture.  
 Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
 Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Graphite	7782-42-5	TWA (Respirable)	2.5 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
Talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m <sup>3</sup>	NIOSH REL
		TWA (Res-	2 mg/m <sup>3</sup>	ACGIH

**2000® NM**

Version 1.3      Revision Date: 09/04/2015      SDS Number: 117291-00003      Date of last issue: 08/18/2015  
 Date of first issue: 05/18/2015

		pirable frac- tion)		
Calcium oxide	1305-78-8	TWA	2 mg/m <sup>3</sup>	ACGIH
		TWA	2 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA Z-1
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m <sup>3</sup>	ACGIH
Quartz	14808-60-7	TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL

**Occupational exposure limits of decomposition products**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium hydroxide	1305-62-0	TWA	5 mg/m <sup>3</sup>	ACGIH
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	5 mg/m <sup>3</sup>	NIOSH REL

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.  
 Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

**Personal protective equipment**

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

circumstance where air purifying respirators may not provide adequate protection.

Hand protection  
Material

: Impervious gloves

Remarks

: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection

: Wear the following personal protective equipment:  
Safety goggles

Skin and body protection

: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures

: Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance

: Viscous semi-solid

Color

: black

Odor

: Petroleum

Odor Threshold

: No data available

pH

: Not applicable (not an aqueous solution)

Melting point/freezing point

: No data available

Initial boiling point and boiling range

: 260 °C  
Method: ASTM D 2887  
Distillates (petroleum), hydrotreated heavy naphthenic

Flash point

: 196 °C  
Method: Cleveland open cup  
Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate

: No data available

Flammability (solid, gas)

: No data available

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	1.2
Density	:	No data available
Solubility(ies)		
Water solubility	:	negligible
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 12.0 mm <sup>2</sup> /s (40 °C) Distillates (petroleum), hydrotreated heavy naphthenic
		> 120 cSt (40 °C) Distillates (petroleum), hydrotreated heavy naphthenic
Flow time	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
Conditions to avoid	:	Exposure to moisture.
Incompatible materials	:	Oxidizing agents Water

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

Hazardous decomposition products  
Contact with water or humid air : Calcium hydroxide

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

**Graphite:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

**Talc:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

**Calcium oxide:**



**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 425  
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**12-Hydroxy lithium stearate:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity

**Quartz:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit  
Result: No skin irritation  
Remarks: Based on data from similar materials

**Graphite:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

**Talc:**

Species: Rabbit  
Result: No skin irritation

**Calcium oxide:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: Skin irritation  
Remarks: Based on data from similar materials

**12-Hydroxy lithium stearate:**

Species: Rabbit  
Result: No skin irritation  
Remarks: Based on data from similar materials

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

Result: No eye irritation  
Remarks: Based on data from similar materials

**Graphite:**

Species: Rabbit  
Result: No eye irritation

**Talc:**

Species: Rabbit  
Result: No eye irritation

**Calcium oxide:**

Species: Rabbit  
Result: Irreversible effects on the eye  
Method: OECD Test Guideline 405

**12-Hydroxy lithium stearate:**

Species: Rabbit  
Result: No eye irritation  
Remarks: Based on data from similar materials

**Respiratory or skin sensitization**

Skin sensitization: Not classified based on available information.  
Respiratory sensitization: Not classified based on available information.

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type: Buehler Test  
Routes of exposure: Skin contact  
Species: Guinea pig  
Result: negative  
Remarks: Based on data from similar materials

**Graphite:**

Test Type: Local lymph node assay (LLNA)  
Routes of exposure: Skin contact  
Species: Mouse  
Result: negative

**Talc:**

Routes of exposure: Skin contact  
Species: Humans  
Result: negative

**12-Hydroxy lithium stearate:**

Test Type: Local lymph node assay (LLNA)  
Routes of exposure: Skin contact  
Species: Mouse  
Method: OECD Test Guideline 429  
Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**2000® NM**

Version 1.3      Revision Date: 09/04/2015      SDS Number: 117291-00003      Date of last issue: 08/18/2015  
Date of first issue: 05/18/2015

---

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Graphite:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Talc:**

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA syn-  
thesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Species: Rat  
Application Route: Ingestion  
Result: negative

**Calcium oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Product:**

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic  
based on DMSO extract content < 3% (Regulation (EC)  
1272/2008, Annex VI, Part 3, Note L).

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Mouse  
Application Route: Skin contact  
Exposure time: 78 weeks  
Method: OECD Test Guideline 451  
Result: negative

**Talc:**

Species: Mouse  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 2 Years  
Result: negative

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

**Calcium oxide:**

Species: Rat  
 Application Route: Ingestion  
 Exposure time: 104 weeks  
 Result: negative  
 Remarks: Based on data from similar materials

**Quartz:**

Species: Humans  
 Application Route: inhalation (dust/mist/fume)  
 Result: positive  
 Remarks: IARC (International Agency for Research on Cancer)  
 The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

**IARC**

Group 1: Carcinogenic to humans

Quartz 14808-60-7

**OSHA**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

Known to be human carcinogen

Quartz 14808-60-7

**Reproductive toxicity**

Not classified based on available information.

**Ingredients:****Graphite:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative

**Talc:**

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

**Calcium oxide:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

**STOT-single exposure**

Not classified based on available information.

**Ingredients:****Calcium oxide:**

Assessment: May cause respiratory irritation.

**STOT-repeated exposure**

Not classified based on available information.

**Ingredients:****12-Hydroxy lithium stearate:**

Routes of exposure: Ingestion  
Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Quartz:**

Routes of exposure: inhalation (dust/mist/fume)  
Target Organs: Lungs  
Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

**Repeated dose toxicity****Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rat  
NOAEL: > 0.98 mg/l  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 28 Days  
Remarks: Based on data from similar materials

**Graphite:**

Species: Rat  
NOAEL: 12 mg/m<sup>3</sup>  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 28 Days  
Method: OECD Test Guideline 412

**12-Hydroxy lithium stearate:**

Species: Rat  
NOAEL: > 88 mg/kg  
Application Route: Ingestion  
Exposure time: 90 Days

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

**Quartz:**

Species: Humans

LOAEL: 0.053 mg/m<sup>3</sup>

Application Route: inhalation (dust/mist/fume)

Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

**Aspiration toxicity**

Not classified based on available information.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
 Exposure time: 21 d  
 Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC: > 1.93 mg/l  
 Exposure time: 10 min  
 Remarks: Based on data from similar materials

**Graphite:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201

Toxicity to bacteria : EC50: > 1,012.5 mg/l

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

Exposure time: 3 h  
Method: OECD Test Guideline 209

**Talc:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l  
Exposure time: 24 h

**Calcium oxide:**

Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : LC50: 158 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 48 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l  
Exposure time: 12 d  
Remarks: Based on data from similar materials

Toxicity to bacteria : EC50: 300.4 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

**12-Hydroxy lithium stearate:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

**Quartz:**

Ecotoxicology Assessment  
Acute aquatic toxicity : No toxicity at the limit of solubility.

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

Chronic aquatic toxicity : No toxicity at the limit of solubility.

**Persistence and degradability****Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**12-Hydroxy lithium stearate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulation****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation**



**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

**49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Acute Health Hazard**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.**US State Regulations****Pennsylvania Right To Know**

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 50 %
Graphite	7782-42-5	20 - 30 %
Polytetrafluoroethylene	9002-84-0	10 - 20 %
Talc	14807-96-6	5 - 10 %
Calcium oxide	1305-78-8	1 - 5 %
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	0.1 - 1 %
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	0.1 - 1 %
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	0.1 - 1 %
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	0.1 - 1 %

**New Jersey Right To Know**

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 50 %
Graphite	7782-42-5	20 - 30 %
Polytetrafluoroethylene	9002-84-0	10 - 20 %
Talc	14807-96-6	5 - 10 %
Calcium oxide	1305-78-8	1 - 5 %
Quartz	14808-60-7	0.1 - 1 %

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer.

**2000® NM**

Version 1.3      Revision Date: 09/04/2015      SDS Number: 117291-00003      Date of last issue: 08/18/2015  
 Date of first issue: 05/18/2015


Quartz

14808-60-7

**The ingredients of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**SECTION 16. OTHER INFORMATION****Further information****NFPA:****HMIS III:**

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

(Q)SAR - (Quantitative) Structure Activity Relationship; ASTM - American Society for the Testing of Materials; bw - Body weight; DIN - Standard of the German Institute for Standardisation; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardi-

**2000® NM**

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2015
1.3	09/04/2015	117291-00003	Date of first issue: 05/18/2015

---

zation; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative; DSL - Domestic Substances List (Canada); KECI - Korea Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); AICS - Australian Inventory of Chemical Substances; IECSC - Inventory of Existing Chemical Substances in China; ENCS - Existing and New Chemical Substances (Japan); ISHL - Industrial Safety and Health Law (Japan); PICCS - Philippines Inventory of Chemicals and Chemical Substances; NZIoC - New Zealand Inventory of Chemicals; TCSI - Taiwan Chemical Substance Inventory; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; DOT - Department of Transportation; EHS - Extremely Hazardous Substance; HMIS - Hazardous Materials Identification System; MSHA - Mine Safety and Health Administration; NFPA - National Fire Protection Association; RCRA - Resource Conservation and Recovery Act; RQ - Reportable Quantity; SARA - Superfund Amendments and Reauthorization Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; GLP - Good Laboratory Practice; ERG - Emergency Response Guide; NTP - National Toxicology Program; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/04/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8