

SAFETY DATA SHEET



4010® NM

Version Revision Date: MSDS Number: Date of last issue: -
1.0 04.06.2015 150443-00001 Date of first issue: 04.06.2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 4010® NM
Product code : 000000000000658051
SDS-Identcode : 504G

Manufacturer or supplier's details

Company : Bestolife Corporation
Address : 2777 N. Stemmons Frwy Ste 1800
 Dallas TX 75207,
Telephone : 855-243-9164/972-865-8961
Emergency telephone number : CHEMTREC: 800-101-2201, International: +1-703-527-3887
Telefax : 214-631-3047

Recommended use of the chemical and restrictions on use


Recommended use : Industrial use
 Thread Compound (Pipe Dope) and Jacking grease for use in
 Offshore industries
 Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-
 pheres.

2. HAZARDS IDENTIFICATION

GHS Classification

Serious eye damage/eye irri- : Category 2
tation

GHS Label element

Hazard pictograms : 

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

SAFETY DATA SHEET



4010® NM

Version 1.0 Revision Date: 04.06.2015 MSDS Number: 150443-00001 Date of last issue: -
Date of first issue: 04.06.2015

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 30 - < 50
Graphite	7782-42-5	>= 10 - < 20
Talc	14807-96-6	>= 1 - < 10
Calcium carbonate	471-34-1	>= 1 - < 10
Calcium fluoride	7789-75-5	>= 1 - < 10
Calcium acetate	62-54-4	>= 1 - < 10
Titanium dioxide	13463-67-7	>= 1 - < 10
Calcium oxide	1305-78-8	>= 1 - < 10
Quartz	14808-60-7	>= 0.1 - < 1

4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.

SAFETY DATA SHEET



4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides
Fluorine compounds
Oxides of phosphorus

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labelled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	PEL (long term) (Mist)	5 mg/m ³	SG OEL
		PEL (short term) (Mist)	10 mg/m ³	SG OEL
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
Graphite	7782-42-5	PEL (long term) (Respirable dust)	2 mg/m ³	SG OEL

SAFETY DATA SHEET



4010® NM

Version 1.0 Revision Date: 04.06.2015 MSDS Number: 150443-00001 Date of last issue: -
Date of first issue: 04.06.2015

		TWA (Respirable fraction)	2 mg/m ³	ACGIH
Talc	14807-96-6	PEL (long term)	2 mg/m ³	SG OEL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
Calcium carbonate	471-34-1	PEL (long term)	10 mg/m ³	SG OEL
Calcium fluoride	7789-75-5	PEL (long term)	2.5 mg/m ³ (Fluorine)	SG OEL
		TWA	2.5 mg/m ³ (Fluorine)	ACGIH
Titanium dioxide	13463-67-7	PEL (long term)	10 mg/m ³	SG OEL
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
Calcium oxide	1305-78-8	PEL (long term)	2 mg/m ³	SG OEL
		TWA	2 mg/m ³	ACGIH
Quartz	14808-60-7	PEL (long term) (Respirable dust)	0.1 mg/m ³	SG OEL
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium hydroxide	1305-62-0	PEL (long term)	5 mg/m ³	SG OEL
		TWA	5 mg/m ³	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Calcium fluoride	7789-75-5	Fluoride (Fluorine)	Urine	Prior to shift (16 hours after exposure ceases)	2 mg/l	ACGIH BEI
		Fluoride (Fluorine)	Urine	End of shift (As soon as possible after exposure ceases)	3 mg/l	ACGIH BEI

SAFETY DATA SHEET



4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Particulates type

Hand protection
Material : Impervious gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous semi-solid

Colour : light grey

Odour : Petroleum

Odour Threshold : No data available

pH : Not applicable (not an aqueous solution)

: No data available

SAFETY DATA SHEET



4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Initial boiling point and boiling range : 208 °C

Flash point : 160 °C
Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 1.3

Density : No data available

Solubility(ies)
Water solubility : negligible

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : 2.085 mm²/s (40 °C)
20.85 cSt (40 °C)

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.
Hazardous decomposition products will be formed upon contact with water or humid air.

Conditions to avoid : Exposure to moisture

Incompatible materials : Oxidizing agents
Water

Hazardous decomposition products
Contact with water or humid air : Calcium hydroxide

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Calcium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Calcium fluoride:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.07 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Calcium acetate:

Acute oral toxicity : LD50 (Rat, female): 1,943 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Calcium oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Species: Rabbit
Result: No skin irritation

Graphite:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Talc:

Species: Rabbit
Result: No skin irritation

Calcium carbonate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Calcium fluoride:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Calcium acetate:

Species: Rabbit

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Result: No skin irritation

Titanium dioxide:

Species: Rabbit

Result: No skin irritation

Calcium oxide:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Species: Rabbit

Result: No eye irritation

Graphite:

Species: Rabbit

Result: No eye irritation

Talc:

Species: Rabbit

Result: No eye irritation

Calcium carbonate:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Calcium fluoride:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Calcium acetate:

Species: Rabbit

Result: No eye irritation

Titanium dioxide:

Species: Rabbit

Result: No eye irritation

Calcium oxide:

Species: Rabbit

Result: Irreversible effects on the eye

Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Method: OECD Test Guideline 474
Result: negative

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Rat
Application Route: Ingestion
Result: negative

Calcium carbonate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Calcium fluoride:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Calcium acetate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated light naphthenic:

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Result: negative

Talc:

Species: Mouse
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 Years
Result: negative

Calcium fluoride:

Species: Rat
Application Route: Ingestion
Exposure time: 99 weeks
Result: negative

Titanium dioxide:

Species: Rat
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 Years
Method: OECD Test Guideline 453
Result: positive

Remarks: The mechanism or mode of action may not be relevant in humans.
The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Calcium oxide:

Species: Rat
Application Route: Ingestion
Exposure time: 104 weeks
Result: negative
Remarks: Based on data from similar materials

Quartz:

Species: Humans
Application Route: inhalation (dust/mist/fume)
Result: positive
Remarks: IARC (International Agency for Research on Cancer)
The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Reproductive toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

- test
 Species: Rat
 Application Route: Ingestion
 Result: negative
- Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Skin contact
 Result: negative
- Graphite:**
 Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
- Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
- Talc:**
 Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Ingestion
 Result: negative
- Calcium carbonate:**
 Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
- Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 414
 Result: negative
- Calcium fluoride:**
 Effects on fertility : Test Type: Two-generation reproduction toxicity study
 Species: Rat
 Application Route: Ingestion
 Result: negative
- Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Ingestion

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Result: negative

Calcium acetate:

Effects on fertility

: Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development

: Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Calcium oxide:

Effects on foetal development

: Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT - single exposure

Not classified based on available information.

Components:**Calcium oxide:**

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:**Calcium fluoride:**

Exposure routes: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Quartz:

Exposure routes: inhalation (dust/mist/fume)

Target Organs: Lungs

Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Distillates (petroleum), hydrotreated light naphthenic:**

Species: Rabbit

NOAEL: 1,000 mg/kg

Application Route: Skin contact

Exposure time: 4 w

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Method: OECD Test Guideline 410

Graphite:

Species: Rat
NOAEL: 12 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 d
Method: OECD Test Guideline 412

Calcium carbonate:

Species: Rat
NOAEL: 1,000 mg/kg
Application Route: Ingestion
Exposure time: 28 d
Method: OECD Test Guideline 422

Calcium fluoride:

Species: Rat
NOAEL: 7 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 d

Calcium acetate:

Species: Rat
NOAEL: >= 3,600 mg/kg
Application Route: Ingestion
Exposure time: 28 d
Remarks: Based on data from similar materials

Titanium dioxide:

Species: Rat
NOAEL: 24,000 mg/kg
Application Route: Ingestion
Exposure time: 28 d

Species: Rat

NOAEL: 10 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 y
Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Quartz:

Species: Humans
LOAEL: 0.053 mg/m³
Application Route: inhalation (dust/mist/fume)
Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Distillates (petroleum), hydrotreated light naphthenic:**

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
- Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
- Toxicity to bacteria : NOEC (Photobacterium phosphoreum): > 2.17 mg/l
Exposure time: 4 d

Graphite:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to bacteria : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Talc:

- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
Exposure time: 24 h

Calcium carbonate:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to bacteria : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- Calcium fluoride:**
- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 108 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 97 - 270 mg/l
Exposure time: 48 h
- Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 122 mg/l
Exposure time: 96 h
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 4 mg/l
Exposure time: 21 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 8.9 mg/l
Exposure time: 21 d
- Calcium acetate:**
- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 919 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): > 1,000 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials
- NOEC (Skeletonema costatum (marine diatom)): 1,000 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials
- Toxicity to bacteria : EC50 (Pseudomonas putida): 7,200 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials
- Titanium dioxide:**
- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h

Toxicity to bacteria : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Calcium oxide:

Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : LC50: 158 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 48 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l
Exposure time: 12 d
Remarks: Based on data from similar materials

Toxicity to bacteria : EC50: 300.4 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Persistence and degradability**Components:****Distillates (petroleum), hydrotreated light naphthenic:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Calcium acetate:

Biodegradability : Result: Readily biodegradable

SAFETY DATA SHEET



4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

Biodegradation: 99 %
Exposure time: 28 d
Remarks: Based on data from similar materials

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

International Regulation

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and : Not applicable
Environmental Protection and Management (Hazardous Substances) Regulations

The components of this product are reported in the following inventories:

4010® NM

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	04.06.2015	150443-00001	Date of first issue: 04.06.2015

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

16. OTHER INFORMATION**Further information**

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
SG OEL : Singapore. Workplace Safety and Health Act - First Schedule Permissible Exposure Limits of Toxic Substances
ACGIH / TWA : 8-hour, time-weighted average
SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term
SG OEL / PEL (short term) : Permissible Exposure Level (PEL) Short Term

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

SG / EN