

SAFETY DATA SHEET



COPPER SUPREME SPECIAL BLEND® PLUS

Version 1.0 Revision Date: 26.05.2015 MSDS Number: 131401-00001 Date of last issue: -
Date of first issue: 26.05.2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : COPPER SUPREME SPECIAL BLEND® PLUS
Product code : 000000000000635086
SDS-Identcode : 476G

Manufacturer or supplier's details

Company : Bestolife Corporation
Address : 2777 N. Stemmons Frwy Ste 1800
Dallas TX 75207,
Telephone : 855-243-9164/972-865-8961
Emergency telephone number : CHEMTREC: 800-101-2201, International: +1-703-527-3887
Telefax : 214-631-3047

Recommended use of the chemical and restrictions on use


Recommended use : Industrial use
Thread Compound (Pipe Dope) and Jacking grease for use in
Offshore industries
Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-
pheres.

2. HAZARDS IDENTIFICATION

GHS Classification

Serious eye damage/eye irri- : Category 2
tation

GHS Label element

Hazard pictograms : 

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

SAFETY DATA SHEET



COPPER SUPREME SPECIAL BLEND® PLUS

Version 1.0 Revision Date: 26.05.2015 MSDS Number: 131401-00001 Date of last issue: -
Date of first issue: 26.05.2015

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 20 - < 30
Graphite	7782-42-5	>= 10 - < 20
Copper	7440-50-8	>= 10 - < 20
Talc	14807-96-6	>= 1 - < 10
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	>= 1 - < 10
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 1 - < 10
Calcium oxide	1305-78-8	>= 1 - < 10
Antimony, dialkyl dithiocarbamate	15890-25-2	>= 1 - < 10
Calcium bis(dinonylnaphthalenesulphonate)	57855-77-3	>= 1 - < 10
Quartz	14808-60-7	>= 0.1 - < 1
Hydrogen sulfide	7783-06-4	>= 0.1 - < 1

4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)
Sulphur oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labelled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	PEL (long term) (Mist)	5 mg/m ³	SG OEL
		PEL (short	10 mg/m ³	SG OEL

SAFETY DATA SHEET



COPPER SUPREME SPECIAL BLEND® PLUS

Version 1.0 Revision Date: 26.05.2015 MSDS Number: 131401-00001 Date of last issue: -
Date of first issue: 26.05.2015

		term) (Mist)		
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	PEL (long term) (Mist)	5 mg/m3	SG OEL
		PEL (short term) (Mist)	10 mg/m3	SG OEL
Graphite	7782-42-5	PEL (long term) (Respirable dust)	2 mg/m3	SG OEL
		TWA (Respirable fraction)	2 mg/m3	ACGIH
Copper	7440-50-8	PEL (long term) (Dusts and mists)	1 mg/m3 (Copper)	SG OEL
		PEL (long term) (Fumes)	0.2 mg/m3	SG OEL
		TWA (Dust and mist)	1 mg/m3 (Copper)	ACGIH
		TWA (Fumes)	0.2 mg/m3 (Copper)	ACGIH
Talc	14807-96-6	PEL (long term)	2 mg/m3	SG OEL
		TWA (Respirable fraction)	2 mg/m3	ACGIH
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	PEL (long term)	0.5 mg/m3 (antimony)	SG OEL
		TWA	0.5 mg/m3 (antimony)	ACGIH
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	PEL (long term) (Mist)	5 mg/m3	SG OEL
		PEL (short term) (Mist)	10 mg/m3	SG OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Calcium oxide	1305-78-8	PEL (long term)	2 mg/m3	SG OEL
		TWA	2 mg/m3	ACGIH
Antimony, dialkyl dithiocarbamate	15890-25-2	PEL (long term)	0.5 mg/m3 (antimony)	SG OEL
		TWA	0.5 mg/m3 (antimony)	ACGIH
Quartz	14808-60-7	PEL (long term) (Respirable dust)	0.1 mg/m3	SG OEL
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH
Hydrogen sulfide	7783-06-4	PEL (long	10 ppm	SG OEL

COPPER SUPREME SPECIAL BLEND® PLUS

Version 1.0 Revision Date: 26.05.2015 MSDS Number: 131401-00001 Date of last issue: -
Date of first issue: 26.05.2015

		term)	14 mg/m ³	
		PEL (short term)	15 ppm 21 mg/m ³	SG OEL
		TWA	1 ppm	ACGIH
		STEL	5 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium hydroxide	1305-62-0	PEL (long term)	5 mg/m ³	SG OEL
		TWA	5 mg/m ³	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type

Hand protection
Material : Impervious gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Viscous semi-solid
Colour	: dark, copper
Odour	: Petroleum
Odour Threshold	: No data available
pH	: Not applicable (not an aqueous solution)
	: No data available
	: No data available
Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: 1.2
Solubility(ies)	
Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flow time	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

10. STABILITY AND REACTIVITY

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
Conditions to avoid	: Exposure to moisture
Incompatible materials	: Oxidizing agents Water
Hazardous decomposition products	
Contact with water or humid air	: Calcium hydroxide

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Calculation method

Acute toxicity estimate: > 20000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Calculation method

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Copper:

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Calcium oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Calcium bis(dinonylnaphthalenesulphonate):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 18 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Hydrogen sulfide:

Acute inhalation toxicity : LC50 (Rat): 444 ppm
Exposure time: 4 h

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Test atmosphere: gas

Skin corrosion/irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Graphite:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Copper:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Talc:

Species: Rabbit

Result: No skin irritation

Distillates (petroleum), hydrotreated light naphthenic:

Species: Rabbit

Result: No skin irritation

Calcium oxide:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

Remarks: Based on data from similar materials

Calcium bis(dinonylnaphthalenesulphonate):

Species: Rabbit

Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
Remarks: Based on data from similar materials

Graphite:

Species: Rabbit
Result: No eye irritation

Copper:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Talc:

Species: Rabbit
Result: No eye irritation

Distillates (petroleum), hydrotreated light naphthenic:

Species: Rabbit
Result: No eye irritation

Calcium oxide:

Species: Rabbit
Result: Irreversible effects on the eye
Method: OECD Test Guideline 405

Calcium bis(dinonylnaphthalenesulphonate):

Species: Rabbit
Result: Irritation to eyes, reversing within 21 days
Remarks: Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.
Respiratory sensitisation: Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative
Remarks: Based on data from similar materials

Graphite:

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Test Type: Local lymph node assay (LLNA)
 Exposure routes: Skin contact
 Species: Mouse
 Result: negative

Copper:

Test Type: Maximisation Test (GPMT)
 Exposure routes: Skin contact
 Species: Guinea pig
 Method: OECD Test Guideline 406
 Result: negative

Talc:

Exposure routes: Skin contact
 Species: Humans
 Result: negative

Distillates (petroleum), hydrotreated light naphthenic:

Test Type: Buehler Test
 Exposure routes: Skin contact
 Species: Guinea pig
 Method: OECD Test Guideline 406
 Result: negative

Calcium bis(dinonylnaphthalenesulphonate):

Test Type: Human repeat insult patch test (HRIPT)
 Exposure routes: Skin contact
 Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cyto-genetic assay)
 Species: Mouse
 Application Route: Intraperitoneal injection
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cyto-genetic assay)
 Species: Mouse

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Application Route: Intraperitoneal injection
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

Copper:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
 cytogenetic assay)
 Species: Mouse
 Application Route: Ingestion
 Method: Directive 67/548/EEC, Annex V, B.12.
 Result: negative
 Remarks: Based on data from similar materials

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA syn-
 thesis in mammalian cells (in vitro)
 Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
 Species: Rat
 Application Route: Ingestion
 Result: negative

Distillates (petroleum), hydrotreated light naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 476
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
 cytogenetic assay)
 Species: Mouse
 Application Route: Intraperitoneal injection
 Method: OECD Test Guideline 474
 Result: negative

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Antimony, dialkyl dithiocarbamate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo)

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: Equivocal

Calcium bis(dinonylnaphthalenesulphonate):

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Hydrogen sulfide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: inhalation (gas)
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative
Remarks: Based on data from similar materials

Talc:

Species: Mouse
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 Years
Result: negative

Distillates (petroleum), hydrotreated light naphthenic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Result: negative

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Calcium oxide:

Species: Rat
 Application Route: Ingestion
 Exposure time: 104 weeks
 Result: negative
 Remarks: Based on data from similar materials

Quartz:

Species: Humans
 Application Route: inhalation (dust/mist/fume)
 Result: positive
 Remarks: IARC (International Agency for Research on Cancer)
 The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Reproductive toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy paraffinic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Result: negative
 Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Skin contact
 Method: OECD Test Guideline 414
 Result: negative
 Remarks: Based on data from similar materials

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative

Copper:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Species: Rat
 Application Route: Ingestion
 Result: negative
 Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rabbit
 Application Route: Ingestion
 Result: negative

Talc:
 Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Ingestion
 Result: negative

Distillates (petroleum), hydrotreated light naphthenic:
 Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Skin contact
 Result: negative

Calcium oxide:
 Effects on foetal development : Test Type: Embryo-foetal development
 Species: Mouse
 Application Route: Ingestion
 Method: OECD Test Guideline 414
 Result: negative

Antimony, dialkyl dithiocarbamate:
 Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Result: negative

Calcium bis(dinonylnaphthalenesulphonate):
 Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Result: negative
 Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
 Remarks: Based on data from similar materials

Hydrogen sulfide:
 Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
 Species: Rat
 Application Route: inhalation (gas)
 Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: inhalation (gas)
 Result: negative

STOT - single exposure

Not classified based on available information.

Components:**Calcium oxide:**

Assessment: May cause respiratory irritation.

Hydrogen sulfide:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:**Quartz:**

Exposure routes: inhalation (dust/mist/fume)

Target Organs: Lungs

Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rat

NOAEL: > 0.98 mg/l

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 d

Remarks: Based on data from similar materials

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit
NOAEL: 1,000 mg/kg
Application Route: Skin contact
Exposure time: 4 w
Method: OECD Test Guideline 410
Remarks: Based on data from similar materials

Species: Rat
NOAEL: > 980 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 w

Graphite:

Species: Rat
NOAEL: 12 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 d
Method: OECD Test Guideline 412

Copper:

Species: Rat
NOAEL: \geq 2 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 d

Distillates (petroleum), hydrotreated light naphthenic:

Species: Rabbit
NOAEL: 1,000 mg/kg
Application Route: Skin contact
Exposure time: 4 w
Method: OECD Test Guideline 410

Antimony, dialkyl dithiocarbamate:

Species: Rat
NOAEL: \geq 1,000 mg/kg
Application Route: Ingestion
Exposure time: 54 d

Calcium bis(dinonylnaphthalenesulphonate):

Species: Rat
NOAEL: 95 mg/kg
LOAEL: 298 mg/kg
Application Route: Ingestion
Exposure time: 28 d
Method: OECD Test Guideline 422
Remarks: Based on data from similar materials

Quartz:

Species: Humans
LOAEL: 0.053 mg/m³
Application Route: inhalation (dust/mist/fume)
Remarks: The substance is inextricably bound in the product and therefore does not contribute

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10,250 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 15,470 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 202
- EC50 (Daphnia magna (Water flea)): 30,940 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 70,100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
- NOEC (Selenastrum capricornutum (green algae)): 60,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Toxicity to bacteria : NOEC: > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Graphite:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to bacteria : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Copper:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 297 - 513 µg/l
Exposure time: 96 h

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : LC50 (Ceriodaphnia dubia (water flea)): 66 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 30 - 824 µg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 10

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 16 µg/l
Exposure time: 78 d
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 21.5 - 181 µg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 1

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
Exposure time: 24 h

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.02 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Chronic aquatic toxicity : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Distillates (petroleum), hydrotreated light naphthenic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
Exposure time: 72 h

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Test substance: Water Accommodated Fraction

- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
- Toxicity to bacteria : NOEC (Photobacterium phosphoreum): > 2.17 mg/l
Exposure time: 4 d
- Calcium oxide:**
- Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : LC50: 158 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 48 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l
Exposure time: 12 d
Remarks: Based on data from similar materials
- Toxicity to bacteria : EC50: 300.4 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials
- Antimony, dialkyl dithiocarbamate:**
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.02 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
- M-Factor (Chronic aquatic toxicity) : 1
- Ecotoxicology Assessment
Chronic aquatic toxicity : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Calcium bis(dinonylnaphthalenesulphonate):

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 0.28 mg/l

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility
Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.18 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to bacteria : EC50: 560 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Hydrogen sulfide:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.0144 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp.): 0.12 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Scenedesmus subspicatus): 1.87 mg/l
Exposure time: 24 h

M-Factor (Acute aquatic toxicity) : 10

Toxicity to bacteria : EC50: 29 mg/l
Method: ISO 8192

Persistence and degradability**Product:**

Biodegradability : Result: Readily biodegradable

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Antimony, dialkyl dithiocarbamate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 20 %
Exposure time: 28 d

Calcium bis(dinonylnaphthalenesulphonate):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 17 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Hydrogen sulfide:

Biodegradability : Result: rapidly degradable

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.
Contaminated packaging : Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION**International Regulation****UNRTDG**

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Copper)

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

Class : 9
 Packing group : III
 Labels : 9

IATA-DGR

UN/ID No. : UN 3077
 Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
 (Copper)

Class : 9
 Packing group : III
 Labels : Miscellaneous
 Packing instruction (cargo aircraft) : 956
 Packing instruction (passenger aircraft) : 956

IMDG-Code

UN number : UN 3077
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
 N.O.S.
 (Copper)

Class : 9
 Packing group : III
 Labels : 9
 EmS Code : F-A, S-F
 Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.**

Environmental Protection and Management Act and : Not applicable
 Environmental Protection and Management (Hazardous Substances) Regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

Inventories

COPPER SUPREME SPECIAL BLEND® PLUS

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	131401-00001	Date of first issue: 26.05.2015

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

16. OTHER INFORMATION**Further information**

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
SG OEL : Singapore. Workplace Safety and Health Act - First Schedule
Permissible Exposure Limits of Toxic Substances
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term
SG OEL / PEL (short term) : Permissible Exposure Level (PEL) Short Term

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

SG / EN