

SAFETY DATA SHEET



METAL FREE

Version Revision Date: MSDS Number: Date of last issue: -
1.0 26.05.2015 130279-00001 Date of first issue: 26.05.2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : METAL FREE
Product code : 000000000000652756
SDS-Identcode : 313G

Manufacturer or supplier's details

Company : Bestolife Corporation
Address : 2777 N. Stemmons Frwy Ste 1800
 Dallas TX 75207,
Telephone : 855-243-9164/972-865-8961
Emergency telephone number : CHEMTREC: 800-101-2201, International: +1-703-527-3887
Telefax : 214-631-3047

Recommended use of the chemical and restrictions on use


Recommended use : Industrial use
 Thread Compound (Pipe Dope) and Jacking grease for use in
 Offshore industries
 Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-
 pheres.

2. HAZARDS IDENTIFICATION

GHS Classification

Serious eye damage/eye irri- : Category 2
tation

GHS Label element

Hazard pictograms : 

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

SAFETY DATA SHEET



METAL FREE

Version 1.0 Revision Date: 26.05.2015 MSDS Number: 130279-00001 Date of last issue: -
Date of first issue: 26.05.2015

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 50 - < 70
Graphite	7782-42-5	>= 20 - < 30
Talc	14807-96-6	>= 10 - < 20
Calcium oxide	1305-78-8	>= 1 - < 10
12-Hydroxy lithium stearate	7620-77-1	>= 1 - < 10
Quartz	14808-60-7	>= 1 - < 10
Antimony, dialkyl dithiocarbamate	15890-25-2	>= 0.1 - < 1

4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Fluorine compounds
Metal oxides
Silicon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
 Do not swallow.
 Do not get in eyes.
 Handle in accordance with good industrial hygiene and safety practice.
 Keep away from water.
 Protect from moisture.
 Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labelled containers.
 Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	PEL (long term) (Mist)	5 mg/m ³	SG OEL
		PEL (short term) (Mist)	10 mg/m ³	SG OEL
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
Graphite	7782-42-5	PEL (long term) (Respirable dust)	2 mg/m ³	SG OEL
		TWA (Respirable frac-	2 mg/m ³	ACGIH

SAFETY DATA SHEET



METAL FREE

Version 1.0 Revision Date: 26.05.2015 MSDS Number: 130279-00001 Date of last issue: -
Date of first issue: 26.05.2015

Talc	14807-96-6	tion) PEL (long term)	2 mg/m ³	SG OEL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
Calcium oxide	1305-78-8	PEL (long term)	2 mg/m ³	SG OEL
		TWA	2 mg/m ³	ACGIH
12-Hydroxy lithium stearate	7620-77-1	PEL (long term)	10 mg/m ³	SG OEL
		TWA	10 mg/m ³	ACGIH
Quartz	14808-60-7	PEL (long term) (Respirable dust)	0.1 mg/m ³	SG OEL
		TWA (Respirable fraction) (Silica)	0.025 mg/m ³	ACGIH
Antimony, dialkyl dithiocarbamate	15890-25-2	PEL (long term)	0.5 mg/m ³ (antimony)	SG OEL
		TWA	0.5 mg/m ³ (antimony)	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium hydroxide	1305-62-0	PEL (long term)	5 mg/m ³	SG OEL
		TWA	5 mg/m ³	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type

Hand protection
Material : Impervious gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous semi-solid

Colour : black

Odour : Petroleum

Odour Threshold : No data available

pH : Not applicable (not an aqueous solution)

: No data available

: No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 1.2

Solubility(ies)
Water solubility : negligible

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flow time	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available

10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
Conditions to avoid	:	Exposure to moisture
Incompatible materials	:	Oxidizing agents Water
Hazardous decomposition products	:	
Contact with water or humid air	:	Calcium hydroxide

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	:	Skin contact Ingestion Eye contact
--	---	--

Acute toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
---------------------	---	---

Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h
---------------------------	---	---

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Calcium oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Antimony, dialkyl dithiocarbamate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Graphite:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Talc:

Species: Rabbit

Result: No skin irritation

Calcium oxide:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

Graphite:

Species: Rabbit

Result: No eye irritation

Talc:

Species: Rabbit

Result: No eye irritation

Calcium oxide:

Species: Rabbit

Result: Irreversible effects on the eye

Method: OECD Test Guideline 405

12-Hydroxy lithium stearate:

Species: Rabbit

Result: No eye irritation

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Remarks: Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type: Buehler Test

Exposure routes: Skin contact

Species: Guinea pig

Result: negative

Remarks: Based on data from similar materials

Graphite:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse

Result: negative

Talc:

Exposure routes: Skin contact

Species: Humans

Result: negative

12-Hydroxy lithium stearate:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse

Method: OECD Test Guideline 429

Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Rat
Application Route: Ingestion
Result: negative

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Antimony, dialkyl dithiocarbamate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: Equivocal

Carcinogenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative

Talc:

Species: Mouse
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 Years
Result: negative

Calcium oxide:

Species: Rat
Application Route: Ingestion
Exposure time: 104 weeks
Result: negative
Remarks: Based on data from similar materials

Quartz:

Species: Humans
Application Route: inhalation (dust/mist/fume)
Result: positive

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Remarks: IARC (International Agency for Research on Cancer)
The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Reproductive toxicity

Not classified based on available information.

Components:**Graphite:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Talc:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Calcium oxide:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Antimony, dialkyl dithiocarbamate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

STOT - single exposure

Not classified based on available information.

Components:**Calcium oxide:**

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:**12-Hydroxy lithium stearate:**

Exposure routes: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Quartz:

Exposure routes: inhalation (dust/mist/fume)

Target Organs: Lungs

Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rat

NOAEL: > 0.98 mg/l

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 d

Remarks: Based on data from similar materials

Graphite:

Species: Rat

NOAEL: 12 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 d

Method: OECD Test Guideline 412

12-Hydroxy lithium stearate:

Species: Rat

NOAEL: > 88 mg/kg

Application Route: Ingestion

Exposure time: 90 d

Quartz:

Species: Humans

LOAEL: 0.053 mg/m³

Application Route: inhalation (dust/mist/fume)

Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Antimony, dialkyl dithiocarbamate:

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Species: Rat
 NOAEL: >= 1,000 mg/kg
 Application Route: Ingestion
 Exposure time: 54 d

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC: > 1.93 mg/l
 Exposure time: 10 min
 Remarks: Based on data from similar materials

Graphite:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Toxicity to bacteria : EC50: > 1,012.5 mg/l
 Exposure time: 3 h

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Method: OECD Test Guideline 209

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
 Exposure time: 24 h

Calcium oxide:

Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457 mg/l
 Exposure time: 96 h
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : LC50: 158 mg/l
 Exposure time: 96 h
 Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 48 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l
 Exposure time: 12 d
 Remarks: Based on data from similar materials

Toxicity to bacteria : EC50: 300.4 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.02 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment
 Chronic aquatic toxicity : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12-Hydroxy lithium stearate:

Biodegradability : Result: Readily biodegradable
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Antimony, dialkyl dithiocarbamate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 20 %
Exposure time: 28 d

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION**International Regulation****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and : Not applicable
Environmental Protection and Management (Hazardous Substances) Regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

16. OTHER INFORMATION**Further information**

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
SG OEL : Singapore. Workplace Safety and Health Act - First Schedule Permissible Exposure Limits of Toxic Substances
ACGIH / TWA : 8-hour, time-weighted average
SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term
SG OEL / PEL (short term) : Permissible Exposure Level (PEL) Short Term

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided

SAFETY DATA SHEET



METAL FREE

Version	Revision Date:	MSDS Number:	Date of last issue: -
1.0	26.05.2015	130279-00001	Date of first issue: 26.05.2015

ed relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

SG / EN