

BESTOLIFE 3000®



5 Gallon Plastic Pail

PRODUCT CHARACTERISTICS

Color: Black
Penetration: 330-350 (ASTM D 217)
Weight/Gallon: 10.2 pounds/gallon
Dropping Point: 500°F/260°C (typ)
Flash Point: 385°F/196°C (min)
Brushable To: 15°F/-9°C
Friction Factor: 1.0 (per API RP 7A1)*
Contains: Amorphous and synthetic graphite and other non-metallic additives

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
656035	3 1/2 gallon	35 pounds plastic
656050	5 gallon	50 pounds plastic

*API RP 7A 1: "Recommended Practice for Testing of Thread Compound for Rotary-Shouldered Connections" NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

DESCRIPTION

BESTOLIFE 3000® was the first totally non-metal drilling compound, formulated to address environmental concerns as well as the costs of thread compounds with high percentages of heavy metals. The formulation contains a variety of amorphous and synthetic graphite-based materials that combine to make a gasket-like seal to prevent connection washout even under high internal fluid pressures. The use of premium quality, high temperature based grease enhances its performance.

APPLICATIONS

Non-metallic compound for rotary-shouldered connections.

TECHNICAL DATA

BESTOLIFE 3000® has been developed and formulated to address the environmental concerns and costs, related to the use of thread compounds for rotary-shouldered connections that contain high percentages of heavy metals such as lead and zinc. The performance of 3000 is further enhanced through the use of a premium quality, high temperature base grease. This compound has a low environmental impact, coupling with a high level of extreme pressure performance without containing any heavy metal compounds.

NOTES

A material safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

