

BESTOLIFE 72733



3 1/2 Gallon Metal Pail

PRODUCT CHARACTERISTICS

Color: Black-Copper
Penetration: 310-340
Weight/Gallon: 15.8 pounds/gallon
Dropping Point: 350°F/177°C (typ)
Flash Point: 385°F/196°C (min)
Brushable To: 0°F/-18°C
Friction Factor: 1.0*
Contains: Graphite, lead, zinc, copper

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
613150	3 1/2 gallon	50 pounds metal

DESCRIPTION

BESTOLIFE 72733 is a high pressure, high temperature thread compound for casing, tubing, and line pipe that exceeds API RP 5A 3 and obsolete BUL 5A2 and conforms to ISO 13678. It includes a special corrosion inhibitor added to our discontinued 72732 formula for superior corrosion resistance as compared to API Modified.

APPLICATIONS

High-pressure thread compound for casing, tubing, and lining pipe.

TECHNICAL DATA

BESTOLIFE 72733 exceeds the performance requirements and objectives outlined in API RP 5A3*, obsolete API BUL 5A2, and conforms to ISO 13678. This superior thread compound protects connections against galling during make-up and breakout, prevents leakage at temperatures in excess of 300° F, and withstands pressure to 10,000 psi. BESTOLIFE 72733 resists water absorption, disintegration and volume changes, and will not harden, dry out, evaporate or oxidize. It contains special corrosion inhibitors to resist pitting and discoloration of threaded surfaces during field use and storage.

NOTES

A material safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

*API Recommended Practice 5A3: "Recommended Practice on Thread Compounds for Casing, Tubing, and Line Pipe"; Second Edition, July 2003

