

DRILLING COMPOUND

BESTOLIFE No. 270®



3 1/2 Gallon Metal Pail

PRODUCT CHARACTERISTICS

Color: Black
Penetration: 290-310 (ASTM D 217)
Weight/Gallon: 19.6 pounds/gallon
Dropping Point: 350°F/177°C (typ)
Flash Point: 385°F/196°C (min)
Brushable To: 10°F/-12°C
Friction Factor: 1.0 (per API RP 7A1)*
Contains: Over 60% metallic lead and other non-metallic additives

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
600114	1 gallon	14 pounds metal
600150	3 1/2 gallon	50 pounds metal

DESCRIPTION

The original BESTOLIFE No. 270® is a patented formulation for rotary-shouldered connections. It combats galling, seizing, and downhole makeup.

APPLICATIONS

Premium drill collar compound provides maximum protection. Recommended for drill collars, tool joints, casing, tubing, pipe joints, studs, bolts, nuts and screws, gaskets, high temperature flange connections, pumps, exhaust lines and pipeline connections.

TECHNICAL DATA

BESTOLIFE No. 270® is a superior thread compound that contains over 60% pure metallic lead and special non-metallic additives. This premium compound provides maximum protection of drill collars, drill pipe and all threaded connections, except oxygen lines. BESTOLIFE No. 270® provides a stable seal under all conditions and is not attacked by H₂S or drilling fluids. Meets the requirements of API RP SPEC 7: "Specification for Rotary Drill Stem Elements".

NOTES

A material safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

*API RP 7A1: "Recommended Practice for Testing of Thread Compound for Rotary-Shouldered Connections" NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.



BESTOLIFE
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

BESTOLIFE.COM