

BESTOLIFE ZN-60



5 Gallon Metal Pail

PRODUCT CHARACTERISTICS

Color: **Gray**

Penetration: **290-310 (ASTM D 217)**

Weight/Gallon: **16.3 pounds/gallon**

Dropping Point: **350°F/177°C (typ)**

Flash Point: **385°F/196°C (min)**

Brushable To: **10°F/-12°C**

Friction Factor: **1.0 (per API RP 7A1)***

Contains: **Zinc and other non-metallic additives**

PACKAGING

PRODUCT NUMBER	CONTAINER WEIGHT	PRODUCT NUMBER
623340	3 1/2 gallon	40 pounds plastic
623370	5 gallon	70 pounds metal

DESCRIPTION

BESTOLIFE ZN-60 is a zinc-based thread compound recommended for drilling, tool joints, drill collars, and coring bits. It contains 60% finely powdered metallic zinc, plus H₂S and oxidation inhibitors.

APPLICATIONS

Zinc-based thread compound recommended for drilling, tool joints, drill collars, and coring bits.

TECHNICAL DATA

ZN-60 is a zinc-based thread compound made with finely powdered metallic zinc. It contains 60% zinc as well as H₂S and oxidation inhibitors. Meets the requirements of API RP SPEC 7: "Specification for Rotary Drill Stem Elements".

NOTES

A material safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

*API RP 7A1: "Recommended Practice for Testing of Thread Compound for Rotary-Shouldered Connections" NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.



BESTOLIFE
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

BESTOLIFE.COM