

COPPER JOINT



5 Gallon Plastic Pail

PRODUCT CHARACTERISTICS

Color: **Dark Copper**

Penetration: **300-320 (ASTM D 217)**

Weight/Gallon: **10.9 pounds/gallon**

Dropping Point: **350°F/177°C (typ)**

Flash Point: **385°F/196°C (min)**

Brushable To: **10°F/-12°C**

Friction Factor: **1.0 (per API RP 7A1)***

Contains: **Copper, lead, graphite, and other non-metallic additives**

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
630010	1 gallon	10 pounds plastic
630025	3 1/2 gallon	25 pounds plastic
630050	5 gallon	50 pounds plastic

DESCRIPTION

BESTOLIFE Copper Joint (CJ) is a copper/lead-based compound for use on rotary-shouldered connections. CJ seals and protects threaded connections in high temperature and high pressure. It is recommended for drill collars, tool joints, tubing, fishing tools, line pipe connections, flange connections, gaskets, and seals.

APPLICATIONS

Premium drill collar and tool joint compound. Recommended for drill collars, tool joints, tubing, fishing tools, line pipe connections, flange connections, gaskets and seals.

TECHNICAL DATA

BESTOLIFE Copper Joint is a copper, lead, and graphite based compound that seals and protects threaded connections in both high temperatures and high pressures. It can be used on casing and tubing connections as well as drill pipe and collars. Contains H₂S inhibitors.

NOTES

A material safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

*API RP 7A 1: "Recommended Practice for Testing of Thread Compound for Rotary-Shouldered Connections" NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

