

# **COPR 99**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/04/2015

 5.1
 09/24/2015
 115041-00006
 Date of first issue: 05/12/2015

#### **SECTION 1. IDENTIFICATION**

Product name : COPR 99

SDS-Identcode : 503G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation

Address : 2777 N. Stemmons Frwy Ste 1800

Dallas TX 75207,

Telephone : 855-243-9164/972-865-8961

Telefax : 214-631-3047

Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887

(24-hours/7 days)

E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use

Recommended use : Industrial use

Thread Compound (Pipe Dope) and Jacking grease for use in

Offshore industries

Mining, (without offshore industries)

Restrictions on use : Do not use on oxygen lines or in oxygen enriched

atmospheres.

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Skin irritation : Category 2

Eye irritation : Category 2A

**GHS Label element** 

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H315 Causes skin irritation.

H319 Causes serious eye irritation.



## **COPR 99**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/04/2015

 5.1
 09/24/2015
 115041-00006
 Date of first issue: 05/12/2015

Precautionary Statements : Prevention:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

tion.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naph-	64742-52-5	>= 50 - < 70
thenic		
Graphite	7782-42-5	>= 10 - < 20
Talc	14807-96-6	>= 10 - < 20
Copper metal powder	7440-50-8	>= 5 - < 10
12-Hydroxy lithium stearate	7620-77-1	>= 1 - < 5
Calcium oxide	1305-78-8	>= 1 - < 5
Stearic acid	57-11-4	>= 1 - < 5
Lithium Hydroxide Monohydrate	1310-66-3	>= 1 - < 5
Quartz	14808-60-7	>= 0.1 - < 1

#### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

: Causes skin irritation.

Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

: Carbon oxides

Metal oxides

Fluorine compounds

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Follow safe handling advice and personal protective equip-

ment recommendations.

Environmental precautions : Discharge into the environment must be avoided.



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Sweep up or vacuum up spillage and collect in suitable con-

tainer for disposal.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety

practice.

Keep away from water. Protect from moisture.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Graphite	7782-42-5	TWA (Respirable)	2.5 mg/m3	NIOSH REL



# **COPR 99**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/04/2015

 5.1
 09/24/2015
 115041-00006
 Date of first issue: 05/12/2015

		TWA (Respirable fraction)	2 mg/m3	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
Talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA (Respirable fraction)	2 mg/m3	ACGIH
Copper metal powder	7440-50-8	TWA (Dust and mist)	1 mg/m3 (Copper)	ACGIH
		TWA (Fumes)	0.2 mg/m3 (Copper)	ACGIH
		TWA (Dust)	1 mg/m3 (Copper)	NIOSH REL
		TWA (Mist)	1 mg/m3 (Copper)	NIOSH REL
		TWA (dusts and mists)	1 mg/m3 (Copper)	OSHA Z-1
		TWA (Fumes)	0.1 mg/m3 (Copper)	OSHA Z-1
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m3	ACGIH
Calcium oxide	1305-78-8	TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
Stearic acid	57-11-4	TWA	10 mg/m3	ACGIH
Lithium Hydroxide Monohydrate	1310-66-3	CEIL	1 mg/m3	US WEEL
Quartz	14808-60-7	TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respir- able)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Res- pirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

# Occupational exposure limits of decomposition products

•	•	•		
Ingredients	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Calcium hydroxide	1305-62-0	TWA	5 mg/m3	ACGIH
		TWA (total	15 mg/m3	OSHA Z-1
		dust)		
		TWA (respir-	5 mg/m3	OSHA Z-1
		able fraction)		



## **COPR 99**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/04/2015

 5.1
 09/24/2015
 115041-00006
 Date of first issue: 05/12/2015

TWA 5 mg/m3 NIOSH REL

**Engineering measures** 

: Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m3 - respirable particles, 10 mg/m3 - inhalable particles.

### Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Impervious gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Viscous semi-solid

Color : copper, black

Odor : Petroleum

Odor Threshold : No data available

pH : Not applicable (not an aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling

range

: No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 1.2

Solubility(ies)

Water solubility : negligible

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Can react with strong oxidizing agents.

Hazardous decomposition products will be formed upon

contact with water or humid air.

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents

Water

Hazardous decomposition products

Contact with water or hu-

mid air

: Calcium hydroxide

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Skin contact Ingestion Eye contact

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Ingredients:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

**Graphite:** 

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Copper metal powder:

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

12-Hydroxy lithium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Calcium oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 425

Assessment: The substance or mixture has no acute oral tox-

icity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Stearic acid:

Acute oral toxicity : LD50: > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 0.1621 mg/l

Exposure time: 4 h



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

Test atmosphere: vapor

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

**Lithium Hydroxide Monohydrate:** 

Acute oral toxicity : LD50 (Rat): 368 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 6.15 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

# Skin corrosion/irritation

Causes skin irritation.

#### **Ingredients:**

#### Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Graphite:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Talc:

Species: Rabbit

Result: No skin irritation

Copper metal powder:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

12-Hydroxy lithium stearate:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Calcium oxide: Species: Rabbit

Method: OECD Test Guideline 404



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

Result: Skin irritation

Remarks: Based on data from similar materials

Stearic acid: Species: Rabbit

Result: No skin irritation

**Lithium Hydroxide Monohydrate:** 

Result: Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Result: Irritation to eyes, reversing within 21 days

**Ingredients:** 

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

Graphite:

Species: Rabbit

Result: No eye irritation

Talc:

Species: Rabbit

Result: No eye irritation

Copper metal powder:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

12-Hydroxy lithium stearate:

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

Calcium oxide:

Species: Rabbit

Result: Irreversible effects on the eye Method: OECD Test Guideline 405

Stearic acid:

Species: Rabbit

Result: No eye irritation

**Lithium Hydroxide Monohydrate:** 

Result: Irreversible effects on the eye Remarks: Based on skin corrosivity.

# BESTOLIFE PREMIUM COMPOSITION

## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

#### Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

#### Ingredients:

#### Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Remarks: Based on data from similar materials

#### Graphite:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse Result: negative

#### Talc:

Routes of exposure: Skin contact

Species: Humans Result: negative

#### Copper metal powder:

Test Type: Maximization Test Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

#### 12-Hydroxy lithium stearate:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse

Method: OECD Test Guideline 429

Result: negative

#### Stearic acid:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig Result: negative

# **Lithium Hydroxide Monohydrate:**

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

#### Germ cell mutagenicity

Not classified based on available information.

#### **Ingredients:**



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

**Graphite:** 

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro

Species: Rat

Application Route: Ingestion

Result: negative

Copper metal powder:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Method: Directive 67/548/EEC, Annex V, B.12.

Result: negative

Remarks: Based on data from similar materials

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Stearic acid:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

**Lithium Hydroxide Monohydrate:** 

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

#### Carcinogenicity

Not classified based on available information.

**Product:** 

Carcinogenicity - Assess-

ment

: Petroleum distillates have been classified as not carcinogenic

based on DMSO extract content < 3% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note L).

#### **Ingredients:**

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Mouse

Application Route: Skin contact Exposure time: 78 weeks

Method: OECD Test Guideline 451

Result: negative

Talc:

Species: Mouse

Application Route: inhalation (dust/mist/fume)

Exposure time: 2 Years

Result: negative

Calcium oxide:

Species: Rat

Application Route: Ingestion Exposure time: 104 weeks

Result: negative

Remarks: Based on data from similar materials

Quartz:

Species: Humans

Application Route: inhalation (dust/mist/fume)

Result: positive

Remarks: IARC (International Agency for Research on Cancer)

The substance is inextricably bound in the product and therefore does not contribute to a dust

inhalation hazard.

Carcinogenicity - Assess-

ment

: Positive evidence from human epidemiological studies (inhala-

tion)

IARC Group 1: Carcinogenic to humans

Quartz 14808-60-7

**OSHA**No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP Known to be human carcinogen

Quartz 14808-60-7



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

#### Reproductive toxicity

Not classified based on available information.

**Ingredients:** 

**Graphite:** 

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Talc:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Copper metal powder:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rabbit

Application Route: Ingestion

Result: negative

Calcium oxide:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Stearic acid:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat



# **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

**Lithium Hydroxide Monohydrate:** 

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

#### STOT-single exposure

Not classified based on available information.

# **Ingredients:**

#### Calcium oxide:

Assessment: May cause respiratory irritation.

#### STOT-repeated exposure

Not classified based on available information.

#### **Ingredients:**

# 12-Hydroxy lithium stearate:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

#### Quartz:

Routes of exposure: inhalation (dust/mist/fume)

Target Organs: Lungs

Assessment: Shown to produce significant health effects in animals at concentrations of 0.02

mg/l/6h/d or less.

#### Repeated dose toxicity

#### **Ingredients:**

#### Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rat

NOAEL: > 0.98 mg/l

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 Days

Remarks: Based on data from similar materials

# **Graphite:**Species: Rat

NOAEL: 12 mg/m3



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 Days

Method: OECD Test Guideline 412

Copper metal powder:

Species: Rat

NOAEL: >= 2 mg/m3

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 Days

12-Hydroxy lithium stearate:

Species: Rat

NOAEL: > 88 mg/kg

Application Route: Ingestion Exposure time: 90 Days

Stearic acid: Species: Rat

Species: Rat

NOAEL: 1,000 mg/kg Application Route: Ingestion Exposure time: 42 Days

Method: OECD Test Guideline 422

**Lithium Hydroxide Monohydrate:** 

Species: Rat NOAEL: 84 mg/kg

Application Route: Ingestion

Exposure time: 2 yr

Remarks: Based on data from similar materials

Quartz:

Species: Humans LOAEL: 0.053 mg/m3

Application Route: inhalation (dust/mist/fume)

Remarks: The substance is inextricably bound in the product and therefore does not contribute

to a dust inhalation hazard.

**Aspiration toxicity** 

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

**Product:** 

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,064,120

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 16,410 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 202



## **COPR 99**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/04/2015

 5.1
 09/24/2015
 115041-00006
 Date of first issue: 05/12/2015

Remarks: Based on data from similar materials

EC50 (Daphnia magna (Water flea)): 32,820 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 110,268

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Selenastrum capricornutum (green algae)): 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

#### Ingredients:

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC: > 1.93 mg/l

Exposure time: 10 min

Remarks: Based on data from similar materials

**Graphite:** 

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l



## COPR 99

Version **Revision Date:** SDS Number: Date of last issue: 09/04/2015 09/24/2015 115041-00006 Date of first issue: 05/12/2015 5.1

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to bacteria : EC50: > 1,012.5 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l

Exposure time: 24 h

Copper metal powder:

Toxicity to fish : LC50: 10 - < 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Ceriodaphnia dubia (water flea)): 66 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 30 -

824 µg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

M-Factor (Acute aquatic tox-

icity)

: 10

Toxicity to fish (Chronic tox-

icity)

: NOEC: > 1 - 10 μg/l

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

: NOEC (Daphnia magna (Water flea)): 21.5 - 181 μg/l

Exposure time: 21 d

Remarks: Based on data from similar materials

M-Factor (Chronic aquatic

toxicity)

: 10

12-Hydroxy lithium stearate:

Toxicity to fish LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): >

100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Calcium oxide:

Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457

mg/l

Exposure time: 96 h



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

: LC50: 158 mg/l Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 48

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 32 mg/l Exposure time: 12 d

Remarks: Based on data from similar materials

Toxicity to bacteria : EC50: 300.4 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Stearic acid:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 10,000 mg/l

Exposure time: 48 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 4.8 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility.

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.9

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): > 0.22 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: No toxicity at the limit of solubility.

Toxicity to bacteria : EC10 (Pseudomonas putida): 883 mg/l

Exposure time: 16 h

**Lithium Hydroxide Monohydrate:** 

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 109 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203



## **COPR 99**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/04/2015

 5.1
 09/24/2015
 115041-00006
 Date of first issue: 05/12/2015

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 33.5 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 153.44

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

: NOEC (Danio rerio (zebra fish)): 17.35 mg/l

Exposure time: 34 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

: NOEC (Daphnia magna (Water flea)): 4 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to bacteria : EC50: 180.8 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Quartz:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability

**Product:** 

Biodegradability : Result: Readily biodegradable.

Remarks: Based on data from similar materials

Ingredients:

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

12-Hydroxy lithium stearate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 78 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Stearic acid:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 93 % Exposure time: 28 d

Method: OECD Test Guideline 301B



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

#### Bioaccumulative potential

Ingredients:
Stearic acid:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 238 - 288 Remarks: Based on data from similar materials

Partition coefficient: n-

octanol/water

: log Pow: > 5

Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulation

**UNRTDG** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper metal powder)

Class : 9
Packing group : III
Labels : 9

**IATA-DGR** 

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Copper metal powder)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen-

ger aircraft)

: 956

956

22 / 26



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

**IMDG-Code** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper metal powder)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper metal powder)

Class : 9 Packing group : III

Labels : CLASS 9 ERG Code : 171

Marine pollutant : yes (Copper metal powder)

Remarks : Shipment by ground under DOT is non-regulated; however it

may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

#### **SECTION 15. REGULATORY INFORMATION**

#### **EPCRA - Emergency Planning and Community Right-to-Know**

#### **CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Copper metal powder	7440-50-8	5000	83056

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:



# **COPR 99**

**TSCA** 

rsion	Revision Date: 09/24/2015	SDS Number: 115041-00006		last issue: 09/04/2 first issue: 05/12/2	
		Copper metal po	wder	7440-50-8	6.02 %
US S	tate Regulations				
Penn	sylvania Right To Kr	now			
	•	(petroleum), hydrotreate	d heavy	64742-52-5	50 - 70 %
	Graphite			7782-42-5	10 - 20 %
	Talc			14807-96-6	10 - 20 %
	Copper me	etal powder		7440-50-8	5 - 10 %
		uoroethylene		9002-84-0	5 - 10 %
	12-Hydrox	ystearic acid		106-14-9	1 - 5 %
	Calcium o	xide		1305-78-8	1 - 5 %
	Distillates heavy para	(petroleum), solvent-dev affinic	vaxed	64742-65-0	0 - 0.1 %
		(petroleum), hydrotreate	d heavy	64742-54-7	0 - 0.1 %
	Distillates paraffinic	(petroleum), solvent-refi	ned light	64741-89-5	0 - 0.1 %
New	Jersey Right To Kno	w			
	Distillates naphthenic	(petroleum), hydrotreate	d heavy	64742-52-5	50 - 70 %
	Graphite			7782-42-5	10 - 20 %
	Talc			14807-96-6	10 - 20 %
	Copper me	etal powder		7440-50-8	5 - 10 %
	Polytetraflu	uoroethylene		9002-84-0	5 - 10 %
	Calcium ox	xide		1305-78-8	1 - 5 %
	Lithium Hy	droxide Monohydrate		1310-66-3	1 - 5 %
	Quartz	•		14808-60-7	0.1 - 1 %
Califo	ornia Prop. 65	WARNING! This State of Californi		ontains a chemica cancer.	I known in the
	Quartz			14808-60-7	
The i	naredients of this pr	oduct are reported in t	he followi	na inventories:	
DSL	J			luct are on the Ca	nadian DSL
		componente c	p. 00		

Substances.

: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical



## **COPR 99**


 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/04/2015

 5.1
 09/24/2015
 115041-00006
 Date of first issue: 05/12/2015

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

# NFPA:



Special hazard.

#### HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

US WEEL / CEIL : Ceiling

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50



## **COPR 99**

Version Revision Date: SDS Number: Date of last issue: 09/04/2015 5.1 09/24/2015 115041-00006 Date of first issue: 05/12/2015

- Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR -No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

**Data Sheet** 

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/24/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8