

SUPR COPR

Version Revision Date: SDS Number: Date of last issue: 10/29/2015
6.0 12/18/2015 118229-00006 Date of first issue: 05/18/2015

SECTION 1. IDENTIFICATION

Product name : SUPR COPR

SDS-Identcode : 070G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation

Address : 2777 N. Stemmons Frwy Ste 1800
Dallas TX 75207,

Telephone : 855-243-9164/972-865-8961

Telefax : 214-631-3047

Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887
(24-hours/7 days)

E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use

Recommended use : Industrial use
Thread Compound (Pipe Dope) and Jacking grease for use in
Offshore industries
Mining, (without offshore industries)

Restrictions on use : Do not use on oxygen lines or in oxygen enriched
atmospheres.

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Eye irritation : Category 2A

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 - < 50
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 20 - < 30
Talc	14807-96-6	>= 10 - < 20
Copper metal powder	7440-50-8	>= 10 - < 20
Dolomite	16389-88-1	>= 1 - < 5
Calcium oxide	1305-78-8	>= 1 - < 5
Graphite	7782-42-5	>= 1 - < 5
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	>= 1 - < 5
Quartz	14808-60-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
 Remove contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
 If easy to do, remove contact lens, if worn.
 Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention if symptoms occur.

SUPR COPR

Version	Revision Date:	SDS Number:	Date of last issue: 10/29/2015
6.0	12/18/2015	118229-00006	Date of first issue: 05/18/2015

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)
Sulfur oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for : Sweep up or vacuum up spillage and collect in suitable con-

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

containment and cleaning up tainer for disposal.
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Do not get on skin or clothing.
 Do not swallow.
 Do not get in eyes.
 Handle in accordance with good industrial hygiene and safety practice.
 Keep away from water.
 Protect from moisture.
 Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
 Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA (Res-	2 mg/m ³	ACGIH

SUPR COPR

Version
6.0Revision Date:
12/18/2015SDS Number:
118229-00006Date of last issue: 10/29/2015
Date of first issue: 05/18/2015

		pirable fraction)		
Copper metal powder	7440-50-8	TWA (Dust and mist)	1 mg/m ³ (Copper)	ACGIH
		TWA (Fumes)	0.2 mg/m ³ (Copper)	ACGIH
		TWA (Dust)	1 mg/m ³ (Copper)	NIOSH REL
		TWA (Mist)	1 mg/m ³ (Copper)	NIOSH REL
		TWA (dusts and mists)	1 mg/m ³ (Copper)	OSHA Z-1
		TWA (Fumes)	0.1 mg/m ³ (Copper)	OSHA Z-1
Dolomite	16389-88-1	TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
Calcium oxide	1305-78-8	TWA	2 mg/m ³	ACGIH
		TWA	2 mg/m ³	NIOSH REL
		TWA	5 mg/m ³	OSHA Z-1
Graphite	7782-42-5	TWA (Respirable)	2.5 mg/m ³	NIOSH REL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	TWA	0.5 mg/m ³ (antimony)	OSHA Z-1
		TWA	0.5 mg/m ³ (antimony)	ACGIH
		TWA	0.5 mg/m ³ (antimony)	NIOSH REL
Quartz	14808-60-7	TWA (total dust)	30 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL

Occupational exposure limits of decomposition products

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium hydroxide	1305-62-0	TWA	5 mg/m ³	ACGIH
		TWA (total dust)	15 mg/m ³	OSHA Z-1

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA	5 mg/m ³	NIOSH REL

Engineering measures : Processing may form hazardous compounds (see section 10).
 Minimize workplace exposure concentrations.
 Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Impervious gloves

Remarks

: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection

: Wear the following personal protective equipment:
 Safety goggles

Skin and body protection

: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures

: Ensure that eye flushing systems and safety showers are located close to the working place.
 When using do not eat, drink or smoke.

SUPR COPR

Version Revision Date: SDS Number: Date of last issue: 10/29/2015
6.0 12/18/2015 118229-00006 Date of first issue: 05/18/2015

Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous semi-solid

Color : copper

Odor : Petroleum

Odor Threshold : No data available

pH : Not applicable (not an aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : ≥ 200 °C
Method: ASTM D 92, Cleveland open cup
Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 1.2

Density : No data available

Solubility(ies)
 Water solubility : negligible

Partition coefficient: n-
 octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
 Viscosity, dynamic : No data available

 Viscosity, kinematic : No data available

SUPR COPR

Version	Revision Date:	SDS Number:	Date of last issue: 10/29/2015
6.0	12/18/2015	118229-00006	Date of first issue: 05/18/2015

Flow time	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
Conditions to avoid	:	Exposure to moisture.
Incompatible materials	:	Oxidizing agents Water
Hazardous decomposition products	:	
Contact with water or humid air	:	Calcium hydroxide

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Method: OECD Test Guideline 401
 Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
 Method: OECD Test Guideline 402
 Remarks: Based on data from similar materials

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Remarks: Based on data from similar materials

Copper metal powder:

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg
 Method: OECD Test Guideline 423
 Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 436
 Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: The substance or mixture has no acute dermal toxicity

Dolomite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 420
 Assessment: The substance or mixture has no acute oral toxicity
 Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: Based on data from similar materials

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: The substance or mixture has no acute dermal toxicity
 Remarks: Based on data from similar materials

Calcium oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 425
 Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg
 Method: OECD Test Guideline 402
 Assessment: The substance or mixture has no acute dermal toxicity
 Remarks: Based on data from similar materials

Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 401
 Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: The substance or mixture has no acute inhalation toxicity

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
 Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit
 Result: No skin irritation
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit
 Result: No skin irritation
 Remarks: Based on data from similar materials

SUPR COPR

Version Revision Date: SDS Number: Date of last issue: 10/29/2015
6.0 12/18/2015 118229-00006 Date of first issue: 05/18/2015

Talc:

Species: Rabbit
Result: No skin irritation

Copper metal powder:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Dolomite:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
Remarks: Based on data from similar materials

Calcium oxide:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Skin irritation
Remarks: Based on data from similar materials

Graphite:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Result: Irritation to eyes, reversing within 21 days

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
Remarks: Based on data from similar materials

Talc:

Species: Rabbit
Result: No eye irritation

Copper metal powder:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Dolomite:

SUPR COPR

Version Revision Date: SDS Number: Date of last issue: 10/29/2015
6.0 12/18/2015 118229-00006 Date of first issue: 05/18/2015

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
Remarks: Based on data from similar materials

Calcium oxide:

Species: Rabbit
Result: Irreversible effects on the eye
Method: OECD Test Guideline 405

Graphite:

Species: Rabbit
Result: No eye irritation

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.
Respiratory sensitization: Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative
Remarks: Based on data from similar materials

Talc:

Routes of exposure: Skin contact
Species: Humans
Result: negative

Copper metal powder:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Dolomite:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative
Remarks: Based on data from similar materials

Graphite:

SUPR COPR

Version Revision Date: SDS Number: Date of last issue: 10/29/2015
6.0 12/18/2015 118229-00006 Date of first issue: 05/18/2015

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA syn-
thesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Rat
Application Route: Ingestion
Result: negative

Copper metal powder:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: Directive 67/548/EEC, Annex V, B.12.

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
Date of first issue: 05/18/2015

Result: negative
Remarks: Based on data from similar materials

Dolomite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative
Remarks: Based on data from similar materials

Talc:

Species: Mouse
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 Years
Result: negative

Calcium oxide:

Species: Rat
Application Route: Ingestion
Exposure time: 104 weeks
Result: negative
Remarks: Based on data from similar materials

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

||

Quartz:

Species: Humans

Application Route: inhalation (dust/mist/fume)

Result: positive

Remarks: IARC (International Agency for Research on Cancer)

The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

IARC

Group 1: Carcinogenic to humans

Quartz 14808-60-7

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Known to be human carcinogen

Quartz 14808-60-7

Reproductive toxicity

Not classified based on available information.

Ingredients:**Distillates (petroleum), hydrotreated heavy paraffinic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Result: negative
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
 Species: Rat
 Application Route: Skin contact
 Method: OECD Test Guideline 414
 Result: negative
 Remarks: Based on data from similar materials

Talc:

Effects on fetal development : Test Type: Embryo-fetal development
 Species: Rat
 Application Route: Ingestion
 Result: negative

Copper metal powder:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
 Species: Rat
 Application Route: Ingestion
 Result: negative
 Remarks: Based on data from similar materials

SUPR COPR

Version Revision Date: SDS Number: Date of last issue: 10/29/2015
6.0 12/18/2015 118229-00006 Date of first issue: 05/18/2015

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Result: negative

Dolomite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Calcium oxide:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

STOT-single exposure

Not classified based on available information.

Ingredients:**Calcium oxide:**

Assessment: May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

SUPR COPR

Version Revision Date: SDS Number: Date of last issue: 10/29/2015
6.0 12/18/2015 118229-00006 Date of first issue: 05/18/2015

Ingredients:**Quartz:**

Routes of exposure: inhalation (dust/mist/fume)

Target Organs: Lungs

Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rat

NOAEL: > 0.98 mg/l

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 Days

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit

NOAEL: 1,000 mg/kg

Application Route: Skin contact

Exposure time: 4 Weeks

Method: OECD Test Guideline 410

Remarks: Based on data from similar materials

Species: Rat

NOAEL: > 980 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 4 Weeks

Copper metal powder:

Species: Rat

NOAEL: \geq 2 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 Days

Dolomite:

Species: Mouse

NOAEL: 1,300 mg/kg

Application Route: Ingestion

Exposure time: 28 Days

Remarks: Based on data from similar materials

Graphite:

Species: Rat

NOAEL: 12 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 Days

Method: OECD Test Guideline 412

Quartz:

Species: Humans

LOAEL: 0.053 mg/m³

Application Route: inhalation (dust/mist/fume)

SUPR COPR

Version Revision Date: SDS Number: Date of last issue: 10/29/2015
6.0 12/18/2015 118229-00006 Date of first issue: 05/18/2015

Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10,250 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 15,470 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- EC50 (Daphnia magna (Water flea)): 30,940 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 70,100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Selenastrum capricornutum (green algae)): 60,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC: > 1.93 mg/l
 Exposure time: 10 min
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211
 Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC: > 1.93 mg/l
 Exposure time: 10 min
 Method: DIN 38 412 Part 8
 Remarks: Based on data from similar materials

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
 Exposure time: 24 h

Copper metal powder:

Toxicity to fish : LC50: > 10 - 100 µg/l
 Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 10

Toxicity to fish (Chronic toxicity) : NOEC: > 1 - 10 µg/l

M-Factor (Chronic aquatic toxicity) : 10

Dolomite:

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

- Toxicity to fish** : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: No toxicity at the limit of solubility.
 Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates** : EC50 (Daphnia magna (Water flea)): > 16.6 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202
 Remarks: No toxicity at the limit of solubility.
 Based on data from similar materials
- Toxicity to algae** : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Calcium oxide:

- Toxicity to fish** : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457 mg/l
 Exposure time: 96 h
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates** : LC50: 158 mg/l
 Exposure time: 96 h
 Remarks: Based on data from similar materials
- Toxicity to algae** : EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 48 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)** : NOEC: 32 mg/l
 Exposure time: 12 d
 Remarks: Based on data from similar materials
- Toxicity to bacteria** : EC50: 300.4 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

Graphite:

- Toxicity to fish** : LC50 (Danio rerio (zebra fish)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates** : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Toxicity to bacteria : EC50: > 1,012.5 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.02 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211
 Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Chronic aquatic toxicity : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Quartz:**Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability**Product:**

Biodegradability : Result: Readily biodegradable.
 Remarks: Based on data from similar materials

Ingredients:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 31 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

Biodegradability : Result: Not readily biodegradable.
 Remarks: Based on data from similar materials

SUPR COPR

Version	Revision Date:	SDS Number:	Date of last issue: 10/29/2015
6.0	12/18/2015	118229-00006	Date of first issue: 05/18/2015

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.
------------------------	---	---

SECTION 14. TRANSPORT INFORMATION**International Regulation****UNRTDG**

UN number	:	UN 3077
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Copper metal powder, Hydrogen sulfide)

Class	:	9
Packing group	:	III
Labels	:	9

IATA-DGR

UN/ID No.	:	UN 3077
Proper shipping name	:	Environmentally hazardous substance, solid, n.o.s. (Copper metal powder, Hydrogen sulfide)

Class	:	9
Packing group	:	III
Labels	:	Miscellaneous
Packing instruction (cargo aircraft)	:	956
Packing instruction (passenger aircraft)	:	956

IMDG-Code

UN number	:	UN 3077
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Copper metal powder, Hydrogen sulfide)

Class	:	9
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F

SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number : UN 3077
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 (Copper metal powder, Hydrogen sulfide)
 Class : 9
 Packing group : III
 Labels : CLASS 9
 ERG Code : 171
 Marine pollutant : yes (Copper metal powder, Hydrogen sulfide)
 Remarks : Above applies only to containers over 119 gallons or 450 liters.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Copper metal powder	7440-50-8	5000	33060
Ammonia	7664-41-7	100	*
Hydrogen sulfide	7783-06-4	100	177936

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ammonia	7664-41-7	100	*
Hydrogen sulfide	7783-06-4	100	177936

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Copper metal powder 7440-50-8 15.124 %

SUPR COPR

Version	Revision Date:	SDS Number:	Date of last issue: 10/29/2015
6.0	12/18/2015	118229-00006	Date of first issue: 05/18/2015

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	2.0816 %
Antimony, dialkyl dithiocarbamate	15890-25-2	0.45 %

US State Regulations**Pennsylvania Right To Know**

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 50 %
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	20 - 30 %
Copper metal powder	7440-50-8	10 - 20 %
Talc	14807-96-6	10 - 20 %
Hydroxystearate sebacate lithium complexes	68815-49-6	5 - 10 %
Dolomite	16389-88-1	1 - 5 %
Calcium oxide	1305-78-8	1 - 5 %
Graphite	7782-42-5	1 - 5 %
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	0 - 0.1 %
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	0 - 0.1 %
Hydrogen sulfide	7783-06-4	0 - 0.1 %
Ammonia	7664-41-7	0 - 0.1 %

New Jersey Right To Know

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 50 %
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	20 - 30 %
Copper metal powder	7440-50-8	10 - 20 %
Talc	14807-96-6	10 - 20 %
Hydroxystearate sebacate lithium complexes	68815-49-6	5 - 10 %
Calcium oxide	1305-78-8	1 - 5 %
Graphite	7782-42-5	1 - 5 %
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	1 - 5 %
Quartz	14808-60-7	0.1 - 1 %

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

Quartz	14808-60-7
--------	------------

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.


SUPR COPR

Version 6.0 Revision Date: 12/18/2015 SDS Number: 118229-00006 Date of last issue: 10/29/2015
 Date of first issue: 05/18/2015

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration;

SUPR COPR

Version	Revision Date:	SDS Number:	Date of last issue: 10/29/2015
6.0	12/18/2015	118229-00006	Date of first issue: 05/18/2015

n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/18/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8